

Dolce Dekoratif

Velvet Effect

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

Dolce Velvet Effect is a premium decorative effect paint that creates cosmic depth and movement on the surface with metallic pigments, transforming with the light.

PRODUCT DETAILS

Dolce Velvet Effect is a premium decorative effect paint that creates cosmic depth and movement on the surface with metallic pigments, transforming with the light. Fine-textured, metallic and dynamic, with a vivid, high-depth surface in light. Applied with a trowel or special tools in directional movements over a Silikonlu İç Cephe Boyası paint coat. It delivers a durable, aesthetically lasting result on every surface. Areas of use: interior and exterior facades, on all suitable surface-prepared substrates.

FEATURES

- **Multi-dimensional depth with metallic pigments:** Metallic pigments create a cosmic depth and visual richness on the surface.
- **Dynamic surface that shifts with light:** Offers a vivid effect whose tone and movement change with viewing angle and lighting.
- **Strong fit with modern architecture:** Works as a focal surface in prestigious spaces, in harmony with contemporary designs.

AREAS OF USE

- Suitable for interior and exterior use on all suitable surface-prepared substrates.
- The surface must be dry, clean and prepared with a base coat; free of dust and loose residues.

APPLICATION

Base: Applied over a Silikonlu İç Cephe Boyası paint coat after the base is fully dry.

Application method: Applied with a trowel or special tools in directional movements to create metallic movement.

Direction and movement: Keeping the direction of movement produces a consistent, flowing metallic pattern.

Application conditions: Work between +5°C and +35°C; protect the surface from direct sun, wind and precipitation.

SURFACE / TEXTURE

Fine-textured, metallic and dynamic; a vivid, high-depth surface in light.

- Suitable for Exteriors
- Water-Based
- Washable
- Repaintable

Dolce Dekoratif — Velvet Effect

Technical Reference

APPLICATION SYSTEM

1. Surface preparation → 2. Base coat (Silikonlu İç Cephe Boyası base coat) → 3. Velvet Effect — directional effect application → 4. Optional protective topcoat

TECHNICAL DATA

Appearance / form	Viscous liquid
Colour	According to the colour chart
Finish / gloss	Metallic
pH	8 – 9
Density	1.10 – 1.30 g/cm³
Solid content	~40 – 50 %
Viscosity	Medium (viscous)
Flash point	Not applicable (water-based)
Flammability	Non-flammable

COVERAGE

4.67–6 m²/kg

Coverage varies by surface smoothness/absorbency, primer performance, application thickness and the targeted surface character.

DRYING TIME

- Surface Drying: 1–3 hours (depending on ambient conditions)
- Full Cure: 24–72 hours (depending on product type and application thickness)

PACKAGING

1 kg, 2.5 kg, 7.5 kg, 15 kg

STORAGE

Shelf life is 2 years when stored unopened in its original packaging, in a cool, dry place away from direct sunlight (+5˚C to +35˚C).

CLIMATE & REGIONAL GUIDANCE

- Cool / humid or coastal air (high RH): cure and recoat times lengthen — extend intervals, confirm the substrate is dry (< 5 %) and ventilate; do not apply near the dew point.
- Hot / dry inland air: the surface skins quickly — work in shade, avoid midday sun, keep a wet edge and do not over-thin.
- Temperature: apply between +5 °C and +35 °C; cooler slows cure, warmer accelerates it.

APPLICATION CONDITIONS

- Ambient & substrate temperature +5 °C to +35 °C (41–95 °F)
- Relative humidity below 80 %
- Substrate moisture below 5 %
- Do not apply in direct sun, rain, fog or strong wind; protect fresh work for 24–48 h

TOOLS

Trowel / spatula

SUITABLE SUBSTRATES

✓ Prepared interior and exterior walls with a base coat applied
✓ Fully cured, dust-free and even base-coat surface

NOT SUITABLE FOR

✗ Directly on concrete, exposed concrete and cement-based render (without a base coat / primer)
✗ Directly on gypsum board, gypsum plaster and brick (without a base coat / primer)
✗ Continuously wet or water-immersed surfaces
✗ Chalking, friable or non-adhering surfaces (without consolidation)
✗ Frozen, frosty or surfaces below +5 °C

CLEANING

Clean tools with water immediately after use, while the product is still wet.

MAINTENANCE

Clean the cured surface with a soft cloth and a mild, non-abrasive detergent. Avoid aggressive solvents and abrasive pads. Allow full cure before cleaning or heavy use.

ON-SITE REPAIR & TOUCH-UP

1. Clean the damaged area; remove any loose or flaking material.
2. Feather-sand the edges; fill deeper defects with İç Cephe / Dış Cephe Macunu and re-prime if bare substrate is exposed.
3. Re-apply the same product with the original tool/technique, blending outward to a natural break (corner, edge or plane change).
4. Where used, re-apply the protective topcoat over the repaired area.

Decorative finishes may show a slight variation at repair edges; blend to a natural break and keep colour/batch records for accurate matching.

Dolce Dekoratif — Velvet Effect

Safety & Regulatory

HAZARD STATEMENTS

H317 May cause an allergic skin reaction.

Contains: 2-methylisothiazol-3(2H)-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT)

PRECAUTIONARY STATEMENTS

- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P280 Wear protective gloves.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P302+P352 IF ON SKIN: Wash with plenty of soap and water.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P362+P364 Take off contaminated clothing and wash it before reuse.

Note: For more information, please review the product Safety Data Sheet (SDS).

This technical document is based on data obtained under standard laboratory conditions. For matters not specified herein, approval must be obtained from our technical team; otherwise our company cannot be held responsible for application errors arising from incomplete information. We reserve the right to make changes to the content. For detailed risks and precautions regarding health, safety and transport, the Safety Data Sheet (SDS) must be reviewed.

DOLCE PAINT

MDA BOYA VE KİMYA SANAYİ TİCARET LİMİTED ŞİRKETİ

Mehmet Akif Ersoy Mah. Ünvan Sok. No:11-13A Arnavutköy / İstanbul

info@dolceboya.com dolceboya.com

TÜRK MALI